

# AMK-24 SPREADER

Part Number 320200001000



**Optional Accessory:**  
Quick Adjust Chain Package  
Part No. 391200001000



**Optional Accessory:**  
Extended Reach Tip  
Part No. 391000001010  
Order (2) for a pair  
(Increase the spread up to 8 in.)

## SPECIFICATIONS

Maximum Spreader Opening:	24.0 in.	(610 mm)
Maximum Spreader Travel Distance:	23.9 in.	(607 mm)
Weight (Ready-to-use):	37.35 lbs.	(17.0 kg)
Length:	29.7 in.	(754 mm)
Width:	14.0 in.	(356 mm)
Depth:	8.0 in.	(203 mm)
Highest Spreading Force (NFPA 1936, HSF):	10,100 lbs.	(44.8 kN)
Lowest Spreading Force (NFPA 1936, LSF):	9,145 lbs.	(40.6 kN)
Highest Pulling Force (NFPA 1936, HPF):	6,218 lbs.	(27.6 kN)
Lowest Pulling Force (NFPA 1936, LPF):	5,450 lbs.	(24.2 kN)
Maximum Spreading Force (at back of tips):	18,785 lbs.	(83.5 kN)
Rated Input Pressure:	10,500 psi	(724 bar)
Spreader Opening Time:	4 seconds	
Spreader Closing Time:	4 seconds	

## DESIGN & OPERATIONAL FEATURES



*Certified Model NFPA 1936, 2005 edition*

- ★ *Unique construction allows maximum usable force*
- ★ *Tips remain parallel to the cylinder throughout the spread allowing them to stay in contact with the material continuously for maximum spread (helps avoid piercing with the tips)*
- ★ *Removable tips to accept chain package and optional tips for versatility*
- ★ *Push button pins for easy removal of tips (eliminates possibility of losing pins in the field)*
- ★ *Control valve placement provides compact design allowing greater access for the user*
- ★ *Excellent balance and natural hand placement*
- ★ *Anodized for corrosion protection*



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail [experts@amkus.com](mailto:experts@amkus.com)