

EF2S-STD POWER UNIT

Part Number 711201531050



SPECIFICATIONS

Length:	17.6 in.	(447 mm)
Width:	15.1 in.	(384 mm)
Height:	21.9 in.	(556 mm)
Weight (Ready-to-use)	112.7 lbs.	(51 kg)

(Includes hydraulic fluid and couplings)

Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid

Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.20 gpm <small>per port x 2</small>	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm <small>per port x 2</small>	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

 *Certified Model NFPA 1936, 2005 edition*

- ★ *Electric powered, 3.0 horsepower, “Washdown” motor*
- ★ *Two high pressure, two-stage pumping systems*
- ★ *Two 2-Way, 2-position selector valves*
- ★ *Two tools can be connected and operated simultaneously*
- ★ *Non-toxic mineral base hydraulic fluid*
- ★ *Carrying Handle*
- ★ *Also available with roll cage*
- ★ *220/240 Volt single phase*



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com