

# GH2A-MCH MINI POWER UNIT

Part Number 701206516201



## SPECIFICATIONS

|   |              |               |
|---|--------------|---------------|
| Length:   | 18.5 in.     | (470 mm)      |
| Width:  | 15.0 in.     | (381 mm)      |
| Height:   | 18.5 in.     | (470 mm)      |
| Weight (Ready-to-use)                                     | 65.6 lbs.    | (29.8 kg)     |
| (Includes gas, engine oil, hydraulic fluid and couplings) |              |               |
| Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid       |              |               |
| Rated Output Pressure:                                    | 10,500 psi   | (724 bar)     |
| Hydraulic Fluid Reservoir Capacity:                       | .68 gals. US | (2.57 liters) |
| Usable Hydraulic Fluid Capacity:                          | .66 gals. US | (2.50 liters) |
|   |              |               |
| Delivery of pump, stage 1:                                | 0.8 gpm      | (3028 cc/min) |
| Delivery of pump, stage 2:                                | 0.14 gpm     | (530 cc/min)  |

## DESIGN & OPERATIONAL FEATURES

 Certified Model NFPA 1936, 2005 edition

- ★ Gasoline powered 3 horsepower, 4 cycle Honda® engine
- ★ Uses lead free gasoline
- ★ Includes spark arresting muffler
- ★ Two tools can be connected simultaneously
- ★ Alternate tool operation
- ★ Easy access drain port to drain hydraulic fluid from pump
- ★ Easy to fill with large fill port on reservoir
- ★ Non-toxic mineral base hydraulic fluid
- ★ High pressure, two-stage pumping system
- ★ Carrying handle



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226  
Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail [experts@amkus.com](mailto:experts@amkus.com)