

EF2S-XL POWER UNIT

Part Number 711201531040



SPECIFICATIONS

Length	23.0 in.	(584 mm)
Width	16.0 in.	(407 mm)
Width(with one hose loop standard)	19.0 in.	(483 mm)
Height	20.5 in.	(521 mm)
Weight (Ready-to-use)	122.1 lbs.	(55 kg)
(Includes hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.20 gpm <small>per port x 2</small>	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm <small>per port x 2</small>	(946 cc/min)

DESIGN & OPERATIONAL FEATURES



Certified Model NFPA 1936, 2010 edition

- ★ *Electric powered, 3.0 horsepower, “Washdown” motor*
- ★ *Two high pressure, two-stage pumping systems*
- ★ *Two 2-Way, 2-position selector valves*
- ★ *Two tools can be connected and operated simultaneously*
- ★ *Non-toxic mineral base hydraulic fluid*
- ★ *Roll cage for protection and hose storage, also available without roll cage*
- ★ *220/240 Volt single phase*



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com