

# GB2S-XLO POWER UNIT

Part Number 701203512040



## SPECIFICATIONS

Length	23.0 in.	(584 mm)
Width	16.0 in.	(407 mm)
Width (with one hose loop standard)	19.0 in.	(483 mm)
Height	20.5 in.	(521 mm)
Weight (Ready-to-use)	109.6 lbs.	(50 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.20 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

## DESIGN & OPERATIONAL FEATURES



*Certified Model NFPA 1936, 2010 edition*



*EN13204 Designation: MTO*

- ★ *Gasoline powered Briggs & Stratton® overhead valve 4 cycle engine*
- ★ *Uses lead free gasoline*
- ★ *Two high pressure, two-stage pumping systems*
- ★ *Two 2-way, 2-position selector valves*
- ★ *Two tools can be connected and operated simultaneously*
- ★ *Non-toxic mineral base hydraulic fluid*
- ★ *Roll cage for protection and hose storage*



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail [experts@amkus.com](mailto:experts@amkus.com)