

GH2S2-XL POWER UNIT

Part Number 70120G512050



SPECIFICATIONS

Length	23.0 in.	(584 mm)
Width	16.0 in.	(407 mm)
Width (with one hose loop standard)	19.0 in.	(483 mm)
Height	20.5 in.	(521 mm)
Weight (Ready-to-use)	114.0 lbs.	(51.7 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.2 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

 Certified Model NFPA 1936, 2010 edition

 EN13204 Designation: MTO

- ★ Gasoline powered 4 cycle Honda® engine
- ★ Two high pressure, 2-stage pumping systems
- ★ Roll cage for protection and hose storage
- ★ Two tools can be connected and operated simultaneously
- ★ Two 2-way, 2-position selector valves
- ★ High pressure, two-stage pumping system
- ★ Non-toxic mineral base hydraulic fluid
- ★ Uses lead free gasoline



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226
Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com