

GH2S2-XLNT POWER UNIT











Part Number 70120G512051



SPECIFICATIONS

Length	20.5 in.	(521 mm)
Width	16.0 in.	(407 mm)
Width (with one hose loop standard)	18.8 in.	(78 mm)
Height	19.5 in.	(495 mm)
Weight (Ready-to-use)	108.2 lbs.	(49.1 kg)
(Includes gas, engine oil, hydraulic fluid and couplings with no hose loop)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.2 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

-  Certified Model NFPA 1936, 2010 edition
-  EN13204 Designation: MTO
-  Gasoline powered 4 cycle Honda® engine
-  Two high pressure, 2-stage pumping systems
-  Roll cage for protection
-  Two tools can be connected and operated simultaneously
-  Two 2-way, 2-position selector valves
-  High pressure, two-stage pumping system
-  Non-toxic mineral base hydraulic fluid
-  Uses lead free gasoline

