

GH2A-MCH MINI POWER UNIT

Part Number 701206516201



SPECIFICATIONS

Length:	18.5 in.	(470 mm)
Width:	15.0 in.	(381 mm)
Height:	18.5 in.	(470 mm)
Weight (Ready-to-use)	65.6 lbs.	(29.8 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	.68 gals. US	(2.57 liters)
Usable Hydraulic Fluid Capacity:	.66 gals. US	(2.50 liters)
Delivery of pump, stage 1:	0.8 gpm	(3028 cc/min)
Delivery of pump, stage 2:	0.14 gpm	(530 cc/min)

DESIGN & OPERATIONAL FEATURES

 Certified Model NFPA 1936, 2010 edition

 EN13204 Designation: ATO

- ★ Gasoline powered 4 cycle Honda® engine
- ★ Uses lead free gasoline
- ★ Includes spark arresting muffler
- ★ Two tools can be connected simultaneously
- ★ Alternate tool operation
- ★ Easy access drain port to drain hydraulic fluid from pump
- ★ Easy to fill with large fill port on reservoir
- ★ Non-toxic mineral base hydraulic fluid
- ★ High pressure, two-stage pumping system
- ★ Carrying handle



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226

Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com