

GH2S2-STD POWER UNIT

Part Number 701203512052



SPECIFICATIONS

Length	19.5 in.	(495 mm)
Width	15.0 in.	(381 mm)
Height	22.0 in.	(559 mm)
Weight (Ready-to-use)	105 lbs.	(47.6 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.2 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

DESIGN & OPERATIONAL FEATURES

 Certified Model NFPA 1936, 2010 edition

 EN13204 Designation: MTO

- ★ Gasoline powered 4 cycle Honda® engine
- ★ Two high pressure, 2-stage pumping systems
- ★ Carrying handle
- ★ Two tools can be connected and operated simultaneously
- ★ Two 2-way, 2-position selector valves
- ★ Non-toxic mineral base hydraulic fluid
- ★ Uses lead free gasoline



2700 Wisconsin Avenue, Downers Grove, IL 60515-4226
Tel. (630) 515-1800 Fax (630) 515-8866

Website <http://www.amkus.com> E-mail experts@amkus.com