

# GH2S2-XL POWER UNIT











Part Number 701203512050



## SPECIFICATIONS

Length	23.0 in.	(584 mm)
Width	16.0 in.	(407 mm)
Width (with one hose loop standard)	19.0 in.	(483 mm)
Height	20.5 in.	(521 mm)
Weight (Ready-to-use)	114.0 lbs.	(51.7 kg)
(Includes gas, engine oil, hydraulic fluid and couplings)		
Fluid Type: AMKUS MV-1 Mineral Base Hydraulic Fluid		
Rated Output Pressure:	10,500 psi	(724 bar)
Hydraulic Fluid Reservoir Capacity:	2.0 gals. US	(7.6 liters)
Delivery of pump, stage 1:	1.2 gpm per port x 2	(4542 cc/min)
Delivery of pump, stage 2:	0.25 gpm per port x 2	(946 cc/min)

## DESIGN & OPERATIONAL FEATURES

-  *Certified Model NFPA 1936, 2010 edition*
-  *EN13204 Designation: MTO*
-  *Gasoline powered 4 cycle Honda® engine*
-  *Two high pressure, 2-stage pumping systems*
-  *Roll cage for protection and hose storage*
-  *Two tools can be connected and operated simultaneously*
-  *Two 2-way, 2-position selector valves*
-  *High pressure, two-stage pumping system*
-  *Non-toxic mineral base hydraulic fluid*
-  *Uses lead free gasoline*



05/04/10  
Rev. 2

2700 Wisconsin Avenue, Downers Grove, IL 60515-4226  
Tel. (630) 515-1800 Fax (630) 515-8866  
Website <http://www.amkus.com> E-mail [experts@amkus.com](mailto:experts@amkus.com)