



- **6000 lb Hydraulic Lifting Capacity At Full Extension**
- **Easy to Adjust Inner Extension Tubes**
- **Large And Balanced Carrying Handle**
- **Large Anchor Attachment Ring**
- **Multiple Attachment Options In Offset Area**
- **Large Assortment Of Accessories Available**

MODEL	STROKE		LENGTH		WEIGHT	
HLS16 Lifting Strut	15 in	38 cm	61-100 in	155-254 cm	59 lb	26.7 kg
HLS12 Lifting Strut	12 in	30 cm	55-88 in	139-223 cm	52 lb	23.5 kg
TAS45S Telescoping Strut			56-105 in	142-266 cm	30 lb	13.6 kg
TAS44S Telescoping Strut			56-95 in	142-241 cm	27 lb	12.2 kg
TAS34S Telescoping Strut			44-83 in	111-210 cm	24 lb	10.8 kg
TAS33S Telescoping Strut			44-69 in	111-175 cm	20 lb	9.0 kg



## Hand Powered Hydraulic Lifting Strut

The latest technology in vehicle stabilization is available now. Our patent pending design incorporates the strength, speed, control and dependability of hand powered hydraulics integrated into the structural components of the RESCUESTRUT.

### 6000 lb Capacity With Available 15 in Stroke

Don't get caught short. Time is critical in a life saving situation. When needed, a full 15 in lift can be achieved in less than 30 seconds. With our available accessories and end adaptors, most stabilization and lifting situations can be handled with ease.

### RESCUESTRUT are Truly A Multi Use Rescue Tool

With the help of many accessories, our struts transform themselves into other useful tools such as our dash roll kit. Other accessories are available to aid the firefighter in structural collapse and forcible entry. Our Tri-Pod, Bi-Pod and Mono-Pole adaptors extend the usefulness of the RESCUESTRUT for use in rope rescue scenarios.

Telescoping and Lifting Struts



Assorted Heads



Trench Rescue



Vehicle Stabilization

## RESCUESTRUT SPECIFICATIONS

### Hydraulic Lifting Strut

### Telescoping Strut

Lift Capacity	6000 lb	6000 lb	Lengths Available	3 ft	4 ft	5 ft	6 ft
Stroke	15 in	12 in	Holding Capacity	10,000 lb	10,000 lb	10,000 lb	10,000 lb
Weight	59 lb	52 lb	Weight	20 lb	24 lb	27 lb	30 lb
Minimum Height	61 in	55 in	Minimum Height	36 in	48 in	60 in	72 in
Maximum Height	100 in	88 in	Maximum Height	48 in	70 in	84 in	110 in
(Minimum 2:1 safety factor)			(Minimum 2:1 safety factor)				

**AMKUS RESCUE SYSTEMS**  
MADE IN USA • [www.amkus.com](http://www.amkus.com)

4201 Montdale Drive, Valparaiso, IN 46383-4098 USA  
800-592-6587 • 219-548-5000 • Fax 219-476-1669